

Rugged Computer RS A4NX

Computer Vision Edge Unit with NVIDIA Jetson Orin NX (16GB)

preliminary

Rugged Series



Product Highlights

- 24/7 continuous operation
- IP67 protection, extended temperature range
- Power ignition controller
- High shock and vibration resistance
- Resistance to chemicals



Rugged Computer RS A4NX

Order Code RPC/RSA4NX16-A102S-02¹⁵ RPC/RSA4NX16-B102S-02¹⁵

Processor module / Performance		
NVIDIA Jetson Orin NX (16GB RAM) 1024-core NVIDIA Ampere GPU with 32 Tensor Cores 8-core NVIDIA Arm® Cortex A78AE 64-bit CPU	✓	✓
NVIDIA Jetson Orin NX (8GB RAM) 1024-core NVIDIA Ampere GPU with 32 Tensor Cores 6-core NVIDIA Arm® Cortex A78AE 64-bit CPU	on request ¹	on request ¹
AI Performance	100 TOPs	100 TOPs
Memory / Storage		
128-Bit LPDDR5 (102,4 GB/s) RAM soldered on board	16GB	16GB
M.2 2280 Key M socket (for NVMe SSD) ⁶ , an SSD is required, no internal eMMC storage available	240GB	240GB
Features		
Inertial measurement unit (IMU) STMicro ISM330DHCXTR	✓	✓
Real time clock (RTC), with battery backup Renata CR2477 (950 mAh)	✓	✓
Communication Interfaces		
DisplayPort 1.4a @ 8K30 behind the service cover (rear)	1	1
Internal USB version 2.0 behind the service cover (rear), for device flashing and SSH access only (micro USB Type AB)	1	1
USB version 2.0 behind the service cover (rear) (Type A)	2	2
USB version 3.1 (5 Gbit/s) with dustcap (Type A)	1	1
Ethernet 10/100/1000 BASE-T (1× native, 1× I210-IT) (M12 female, x-coded)	2	2
CAN 2.0A / CAN 2.0B (active/passive), CAN FD supported, isolated (M12 female, a-coded)	1	1
Digital I/O's, current sinking, isolated ^{12/24VDC} (M12 male, a-coded)	4in / 2out	4in / 2out
Serial RS232 ¹ , instead of Digital I/Os (M12 male, a-coded)	on request	on request
USB version 2.0 ¹ , instead of Digital I/Os (M12 female, a-coded)	on request	on request
Inertial measurement unit (IMU) STMicro ISM330DHCXTR	1	1
Wireless Connectivity		
Cellular 4G Module (LTE/UMTS/GSM) with GNSS Sierra Wireless EM7590 (Dual nano SIM support)	none	3 × SMA
Wireless LAN (Wi-Fi 6/6E) 802.11ax/ac/a/b/g/n dual-band 2x2 MIMO & Bluetooth 5.2 Intel AX210	none	2 × RP-SMA
Cellular 5G module (4G/3G fallback) with GNSS	on request	on request
High precision multiband GNSS module with optional heading support ¹ u-blox ZED-F9P/F9R	on request	on request
Technical Data		
Dimensions excl. mounting holes [mm]	w196 × h66 × d165	w196 × h66 × d165
Net weight [gram]	~2300	~2350
Non-isolated input voltage with ignition controller and RP protection (M12 male, a-coded)	9 ... 45VDC	9 ... 45VDC
Power consumption ³	~tbd	~tbd
Software / OS		
NVIDIA JetPack SDK – Jetson Linux (Ubuntu based)	✓	✓
Environmental Conditions		
Operating temperature ³	-25°C ... +70°C	-25°C ... +70°C
Storage temperature	-25°C ... +85°C	-25°C ... +85°C
Ingress protection standard according to EN60529	IP67	IP67
Conformal coating ⁴	on request	on request
Shock according to ISO 15003 (designed to meet)	50g peak acc. (11ms)	50g peak acc. (11ms)
Vibration according to ISO 15003 (designed to meet)	2g (10 – 350Hz)	2g (10 – 350Hz)
EMC-Conformity	EN55032 / EN55035	EN55032 / EN55035
Safety (designed to meet)	EN62368-1	EN62368-1
Radio and Telecommunication (designed to meet)	n/a	RED
estimated MTBF @ 25°C ambient ⁵ according to Telcordia SR-332, Environment GB, excluding battery and SSD	~tbd	~tbd

¹ Please contact factory for minimum order quantities

² Internal connector

³ Depending on installation situation and interface connection. Please see user documentation.

⁴ On all possible components (excl. Orin NX module, connectors and wireless devices)

⁵ The product must be ordered with an SSD, use the following order codes: RPC/RMLA4NX16-x202S-02(240GB), -05(480GB), -10(960GB), -20(1920GB)



Product specifications subject to change without notice. All data is for information purposes only and not guaranteed for legal purposes. Information in this data sheet has been carefully checked and is believed to be accurate. However, no responsibility is assumed for inaccuracies. Please refer to the user documentation for additional product specification.